

MPI

Mineral Products, Inc.



The MPI 6260 Multi-Purpose Machine

Rail



Material
Clearing



Cold Air
Blower



Snow and
Ice Clearing



Trenching

All attachments can be changed out
by 2 people in less than 20 minutes.

The 6260 can deposit the spilled material continuously into a dump truck, a rail car that is coupled to the 6260, or to the side of the tracks.



The

V4 Broom

Head

is perfect for railyards and rail tracks with the ability to pick up a variety of material, including, but not limited to, dirt, coal, snow, and rocks. from rail-car spillage.

The **Snow Loading Head**

and

Snow Blower

are designed to remove up to 2,000 tons of snow per hour on a variety of surfaces; railway, railyards, parking lots, and roadways.



The 200hp Snow Blower can cast snow up to 150 feet away, weather depending.

The Snow Blower can rotate 180 degrees right to left.

The Cold Air

Blower

Cleaning those rail switches is no problem for the 6260 Cold Air Blower.



The 200hp Cold Air Blower will produce 9,500 cfm of air with a 275 miles per hour air speed discharge.



The Cold Air Blower has a Flanger attachment that will help clear out buildup of ice.

The trenching head directs the excavated material to the long conveyor for disposal.



The **Trencher** Head

is capable of trenching through concrete, asphalt, rock, dirt or a combination of these.



Interchangeable wheel cutter trencher heads are available in **various widths and diameters**.

The **Swing Conveyor**

has the ability to rotate 180 degrees and be raised from a horizontal discharge position up to approximately 20 degree discharge position.



The Swing conveyor can deposit material right next to the tracks, into a coupled rail car, or even a dump truck.



The 6260 has the ability to

Dump A Coupled Sidecar

No need to detach the coupled sidecar to dump.

The 6260 air system has the ability to air up the sidecar so it can be dumped.



The MPI 6260

Cab



The Operator's Chair and console were ergonomically designed to maximize the operator's comfort and reduce fatigue.



The cab has a hydraulically driven climate control system complete with air prefiltration.

Operator visibility is a top priority. The MPI 6260 has four cameras located around the machine to keep an eye on the machine and the surrounding area.



The

MPI 6260

Multi-Purpose Machine



FRONT ATTACHMENTS:

Material Loading Head

(with or without detachable nylon broom and scarifier)

Snow Loading Head

Sand Loading Head

Trencher *(Wheel Cutters in numerous widths and diameters)*

Cold Air Blower

Asphalt Milling Head

Broom *(11' wide X 36" diameter with hydraulic angle change)*

1250 Gallon De-Icer/Chemical Spray Head with 30-foot folding spray boom

25' Boom Arm *(with 7 different interchangeable attachment heads, below):*

- Fail Mower Head (50" mowing width)
- Tree Trimmer Head (84" cut width, cuts up to 4-3/8" thick limb)
- Saw Blades Tree Trimmer (87" cut width, the four saw blades)
- Ditcher (24" diameter)
- Dual Brush for signal light, sign and reflector post cleaner (20" wide)
- Single Brush Sign Washer (36" wide)
- Tunnel Washing Brush (72" wide with sprays)

has a variety of front and rear attachments which mean the 6260 can work year-around and do an assortment of jobs.



The front attachments can be changed out by two people in approximately 20 minutes.



REAR ATTACHMENTS:

Swing Conveyor

200 hp Snow Blower

200 hp Sand Blower

Wood Chipper
(with 20" X 24" feed chute)

Generator
(single and three phase)

Specifications

The following specifications will vary depending on which Processing Head and Rear Attachment are mounted on the MPI 6260 Multi-Purpose Machine.

Dimensions:

Length: 47'-11" (14.6 meters)
with Wheel Cutter Trencher
Head and Rear Swing
Conveyor Attached

Width: 10' 6" (3.2 meter)

Height: 12'-1" (3.68 meter) minimum
13'-7" (4.14 meter) maximum

Weight (Total):

65,000 lbs. (29,484 kilograms)

Engine:

300 hp (225kilowatt) Cat C7.1 Tier 4
Final diesel

Electrical:

24 volt

Control System:

Danfoss Plus 1

Drive:

Full time four wheel drive

Steering:

- Front wheel only
- Rear wheel only
- All wheel steering
- Crab steering

Tires:

1200 X 24 X 20 ply

Capacities:

Fuel Tank: 100 gallons (378 liter)

Hydraulic Tank: 200 gallons (757 liter)

DEF: 5 gallons (18.9 liter)

Hydraulics:

- Danfoss pumps and motors
- Aeroquip hoses and hose ends

Cab:

- Climate controlled
- Safety glass
- Front and rear wiper and washer
- Deluxe seat with safety belt, right and left control consols with joy sticks and touch screens
- Heated mirrors
- Front and rear lights



MPI

Mineral Products, Inc.

Mailing Address: PO Box 445, 905 Amax Road, Carrier Mills, IL 62917

Plant Address: 905 Amax Road, Carrier Mills, IL 62917

www.mineralproductsinc.com | E-Mail: info@mineralproductsinc.com

Phone: (618) 841-0978 | Fax: (630) 208-1784